

Customer Information Sheet


IF IN DOUBT - ASK

©

NOT TO SCALE

THIRD ANGLE PROJECTION

ALL DIMENSIONS IN mm



Material and coating

Outer conductor	Passivation of stainless steel
Inner conductor	Beryllium copper gold plating
Medium body	PEI

Electrical performance

Characteristic impedance	50Ω
Usage frequency	10MHz~67GHz
Insulation resistance	≥3000MΩ
Dielectric withstand voltage	500Vrms
Contact resistance	Central conductor≤4mΩ, Outer conductor≤2.5mΩ
VSWR	≤1.25
Insertion loss	≤0.1./f(GHz)dB

NAME	ISS.	DATE	CN/CO
APPROVED:			
CHECKED:			
DRAWN:			

HARWIN

www.harwin.com

TOLERANCES

$X. = \pm 1\text{mm}$
 $X.X = \pm 0.50\text{mm}$
 $X.XX = \pm 0.10\text{mm}$
 $X.XXX = \pm 0.01\text{mm}$
 ANGLES = $\pm 5^\circ$
 UNLESS STATED

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.

MATERIAL & FINISH:

TITLE:
KFKG Type, Jack - Jack, Straight Adapter
, 50 ohm

DRAWING NUMBER:
MMCN-1300PN-ST-001

SHT
1
OF
1