

Customer Information Sheet

IF IN DOUBT - ASK







NOT TO SCALE

THIRD ANGLE PROJECTION



ALL DIMENSIONS IN mm

Specifications:

1. Current Rating: 3.2A per pin
2. Contact Resistance: 20mΩ Max
3. Withstand Voltage: 500V AC/DC
4. Insulation Resistance: 1000MΩ Min at 500V DC
5. Operating Temperature: -55°C to + 125°C
6. Insulator (Housing & Cover) Material: LCP, G.F, UL94V-0, Black
7. Contact Material: Copper Alloy
8. Contact Plating:
XXu" Gold on Contact Area (Refer to Ordering Information)
100u" Matte Tin on Solder Area,
50u" Nickel underplating overall
9. Recommended Process:
Wave Soldering,
Peak Temperature: 260±5°C, 5s



T
1.50
2.00
3.00
5.00




PART NUMBER

MMDNX - B3C065 - XX G X

No. of Pins:
10, 12, 16,
20, 26, 30,
40 Pins

Packing:
R = Reel
T = Tube



CL	01	27Jul26	--
NAME	ISS.	DATE	CN/CO
APPROVED:		ML	
CHECKED:		TA	
DRAWN:		CL	

HARWIN

www.harwin.com

GENERAL TOLERANCE

X. = ± 1mm
X.X = ± 0.50mm
X.XX = ± 0.20mm
X.XXX = ± 0.01mm
ANGLES = ±5°
Unless Stated

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.

MATERIAL & FINISH:

SEE ABOVE

TITLE:

2.00mm Pitch Male/Female Integrated BTB Connector, 180° DIP Type

DRAWING NUMBER:

MMDNX-B3C065-XXGX

1 SHT
OF
4

Customer Information Sheet

IF IN DOUBT - ASK




NOT TO SCALE

THIRD ANGLE PROJECTION

ALL DIMENSIONS IN mm

2*05P




2*06P





2*08P




2*10P




2*13P




05




06








08



10



13




2*15P




2*20P




2*30P






15



20



30



CL

01

27Jul26

--

NAME

ISS.

DATE

CN/CO

APPROVED: ML

CHECKED: TA

DRAWN: CL

HARWIN

www.harwin.com

GENERAL TOLERANCE

X. = ± 1mm
X.X = ± 0.50mm
X.XX = ± 0.20mm
X.XXX = ± 0.01mm

ANGLES = ±5°
Unless Stated

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.

MATERIAL & FINISH:

SEE ABOVE

TITLE:

2.00mm Pitch Male/Female Integrated BTB Connector, 180° DIP Type

DRAWING NUMBER:

MMDNX-B3C065-XXGX

2^{SHT}
OF
4

Customer Information Sheet



IF IN DOUBT - ASK





NOT TO SCALE

THIRD ANGLE PROJECTION



ALL DIMENSIONS IN mm



Allowed Angular Transverse



Allowed Angular Longitudinal



CL	01	27Jul26	--
NAME	ISS.	DATE	CN/CO
APPROVED:		ML	
CHECKED:		TA	
DRAWN:		CL	

HARWIN

www.harwin.com

GENERAL TOLERANCE

X. = ± 1mm
X.X = ± 0.50mm
X.XX = ± 0.20mm
X.XXX = ± 0.01mm

ANGLES = ±5°
Unless Stated

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.

MATERIAL & FINISH:

SEE ABOVE

TITLE:

2.00mm Pitch Male/Female Integrated BTB Connector, 180° DIP Type

DRAWING NUMBER:

MMDNX-B3C065-XXGX

3 SHT
OF
4

Customer Information Sheet

IF IN DOUBT - ASK



NOT TO SCALE

THIRD ANGLE PROJECTION

ALL DIMENSIONS IN mm

No. 1:

Before packaging, pay attention to leave more than 160mm(min) empty, after putting the products into the carrier groove, packing with the cover bend then, Note: the tension between tape and cover bend is 30g~120g

No. 2:






Pack the reel in the PE-32 waterproof bag packing,
put 1pc of drying agent,
seal it with vacuum machine and put
it into the inner box
seal it with sealing glue, with labels.

No. 3:

Put inner box into outer box,
(3PCS Inner box/Outer box)
Pay attention to the unified label direction.

No. 4:

Seal, Pack, Label.



Pin	W	S	F
10	24.0 ± 0.30	/	11.50 ± 0.15
12	32.0 ± 0.30	28.40 ± 0.15	14.20 ± 0.15
16	44.0 ± 0.30	40.40 ± 0.15	20.20 ± 0.15
20	44.0 ± 0.30	40.40 ± 0.15	20.20 ± 0.15
26	44.0 ± 0.30	40.40 ± 0.15	20.20 ± 0.15
30	56.0 ± 0.30	52.40 ± 0.15	26.20 ± 0.15
40	72.0 ± 0.30	68.40 ± 0.15	34.20 ± 0.15
60	88.0 ± 0.30	84.40 ± 0.15	42.20 ± 0.15

CL	01	27Jul26	--
NAME	ISS.	DATE	CN/CO
APPROVED:		ML	
CHECKED:		TA	
DRAWN:		CL	



www.harwin.com

GENERAL TOLERANCE

X. = ± 1mm
X.X = ± 0.50mm
X.XX = ± 0.20mm
X.XXX = ± 0.01mm
ANGLES = ± 5°
Unless Stated

THIS DRAWING AND ANY INFORMATION OR
DESCRIPTIVE MATTER SET OUT HEREON ARE
CONFIDENTIAL AND COPYRIGHT PROPERTY
OF THE HARWIN GROUP AND MUST NOT BE
DISCLOSED, LOANED, COPIED OR USED FOR
MANUFACTURING, TENDERING OR FOR ANY
OTHER PURPOSE WITHOUT THEIR WRITTEN
PERMISSION.

MATERIAL & FINISH:

SEE ABOVE

TITLE:

2.00mm Pitch Male/Female Integrated BTB
Connector, 180° DIP Type

DRAWING NUMBER:

MMDNX-B3C065-XXGX

4	SHT
	OF
	4